

Model number	OEM model	SDX-450VP (3.5") SDX-450V/RP (5.25")	SDX-460VP (3.5") SDX-460V/RP (5.25")	SDX-D450V/NB-P	-
	Brand model	AITi100 (5.25")	AITi100-A (5.25")	AITe100	AITe100-UL (V-line)
Type		3.5", 5.25" Internal with dust cover	3.5", 5.25" Internal with dust cover	External with dust cover	External with dust cover
Format	AIT-1 Turbo				
Media	AIT-E Turbo 20GB data cartridge AIT-1 Turbo 40GB data cartridge AIT-1 25GB data cartridge, AIT-1 35GB data cartridge				
Native capacity	40GB (with AIT-1 Turbo 40GB data cartridge)				
Compressed capacity	104GB* (with AIT-1 Turbo 40GB data cartridge)				
Native sustained transfer rate	6MB/s				
Interface	Wide Ultra SCSI LVD/SE	ATA/ATAPI-6 Ultra DMA mode5 (Ultra ATA/100)	Wide Ultra SCSI LVD/SE	IEEE1394(i.LINK S400) USB2.0 (USB1.1(operation with USB1.1 performance))	
Interface configuration	68-pin High density connector	40-pin connector	68-pin High density connector	IEEE1394: 6pin x 2(supporting daisy chain), USB: SeriesB x 1	
Dimensions (Excluding projection)	3.5": 101.6(W) x 41.2(H) x 155(D)mm 5.25": 146(W) x 41.2(H) x 155(D)mm		198(W) x 64.5(H) x 246(D)mm		
Weight	3.5": 740g, 5.25": 970g	3.5": 740g, 5.25": 970g	2.4kg		
Power requirements	DC5V±5% DC12V±10%		AC100V-240V ±10%, 50/60Hz ±5%		
Power consumption (write operation)	10W	7W	20W	20W	

*2.6:1 data compressed with ALDC. The data compression rate varies according to the type of data and the rate is generally lower if the data has already been compressed.

*1kByte=1000Byte, 1MByte=1000kByte, 1GByte=1000MByte basis