

Model number	OEM model	SDX-700VP (3.5") SDX-700V/RP (5.25")	SDX-D700V
	Brand model	AITi260 (5.25")	AITe260
Type	3.5", 5.25" Internal with dust cover		External
Format	AIT-3		
Media	AIT-1 25GB data cartridge, AIT-1 35GB data cartridge AIT-2 36GB data cartridge, AIT-2 50GB data cartridge AIT-3 100GB data cartridge		
Native capacity	100GB (with AIT-3 100GB data cartridge)		
Compressed capacity	260GB* (with AIT-3 100GB data cartridge)		
Native sustained transfer rate	12MB/s (with AIT-3 data cartridge)		
Interface	Ultra 160 SCSI LVD/SE	Ultra 160 SCSI LVD/SE	
Interface configuration	68-pin High density connector	68-pin High density connector	
Dimensions (Excluding projection)	3.5": 101.6(W) x 41.2(H) x 155(D)mm 5.25": 146(W) x 41.2(H) x 155(D)mm	198(W) x 64.5(H) x 246(D)mm	
Weight	3.5": 780g, 5.25": 1,050g	2.4kg	
Power requirements	DC5V±5% DC12V±10%	AC100V-240V ±10%, 50/60Hz ±5%	
Power consumption (write operation)	14W	20W	

*2.6:1 data compressed with ALDC. The data compression rate varies according to the type of data and the rate is generally lower if the data has already been compressed.

*1kByte=1000Byte, 1MByte=1000kByte, 1GByte=1000MByte basis