

Model number	OEM model	SDX-250VP (3.5") SDX-250V/RP (5.25")	SDX-260VP (3.5") SDX-260V/RP (5.25")	SDX-D250V/NB-P
	Brand model	AITi50 (5.25")	AITi50-A (5.25")	AITe50
Type		3.5", 5.25" Internal with dust cover	3.5", 5.25" Internal with dust cover	External with dust cover
Format		AIT-E Turbo		
Media		AIT-E Turbo 20GB data cartridge		
Native capacity		20GB (with AIT-E Turbo 20GB data cartridge)		
Compressed capacity		52GB* (with AIT-E Turbo 20GB data cartridge)		
Native sustained transfer rate		6MB/s		
Interface		Wide Ultra SCSI LVD/SE	ATA/ATAPI-6 Ultra DMA mode5 (Ultra ATA/100)	Wide Ultra SCSI LVD/SE
Interface configuration		68-pin High density connector	40-pin connector	68-pin High density connector
Dimensions (Excluding projection)		3.5": 101.6 (W) x 41.2(H) x 155(D)mm 5.25": 146 (W) x 41.2(H) x 155(D)mm		198(W) x 64.5(H) x 246(D)mm
Weight		3.5": 740g, 5.25": 970g	3.5": 740g, 5.25": 970g	2.4kg
Power requirements		DC5V±5% DC12V±10%		AC100V-240V ± 10%、50/60Hz ± 5%
Power consumption (write operation)		10W	7W	20W

\*2.6:1 data compressed with ALDC. The data compression rate varies according to the type of data and the rate is generally lower if the data has already been compressed.

\*1kByte=1000Byte, 1MByte=1000kByte, 1GByte=1000MByte basis