

Model number	LIB-162/A1	LIB-162/A2	LIB-162/A3	LIB-162/A4
Type	AIT Autoloader		AIT Autoloader	
Number of drives	1 drive (up to 2 drives by option)		1 drive (up to 2 drives by option)	
Number of cartridges	16		16	
Format	AIT-1		AIT-2	
Interface (drive)	WideUltra SCSI LVD/SE		Ultra 160 SCSI LVD/SE	
Interface configuration	68-pin High density connector			
Native capacity	0.56TB		0.8TB	
Compressed capacity	1.46TB *2.6:1 compression		2.08TB *2.6:1 compression	
Native sustained transfer rate	8MB/s (with 2 AIT-1 drives)		12MB/s (with 2 AIT-2 drives)	
MSBF (Mean Swaps Between Failures)	1 million times or more			
Power requirements	AC100-120V ±10%, 50/60Hz AC200-240V +8% -10%, 50/60Hz			
Power consumption	100W (with 2 drives)		120W (with 2 drives)	
Dimensions (Excluding projection)	430(W) x 88(H) x 680(D)mm			
Weight	17.8kg (with 1 drive)			
Main features	<ul style="list-style-type: none"> -Hot-swap drive : can be removed/installed from the front. -Hot-swap fan -High density rack mount backup solution -Cade39 barcode reader -Web-administration -Easy configuration, operation and diagnostics -Easy access loading slot -Automatic shutter -Dust-proof filter 		<ul style="list-style-type: none"> -Hot-swap drive : can be removed/installed from the front. -Hot-swap fan -High density rack mount backup solution -Cade39 barcode reader -R-MIC reader -Web-administration -Easy configuration, operation and diagnostics -Easy access loading slot -Automatic shutter -Dust-proof filter 	
Indicators	<ul style="list-style-type: none"> -128 x 64 dots LCD with backlight, 4 LEDs(Power, Error, Upper/Lower slot) -7-button keypad -Display status of library and drive -Display error message of library and drive -Display warning message of library 			

*2.6:1 data compressed with ALDC. The data compression rate varies according to the type of data and the rate is generally lower if the data has already been compressed.

*1kByte=1000Byte, 1MByte=1000kByte, 1GByte=1000MByte, 1TByte=1000GByte basis