

Model number	LIB-D81/A1	LIB-D81/A2	LIB-D81/A3	LIB-D81/A4
Type	AIT Autoloader		AIT Autoloader	
Number of drives	1	1	1	1
Number of cartridges	8	8	8	8
Format	AIT-1	AIT-2	AIT-3	AIT-4
Interface (drive)	Wide Ultra SCSI LVD/SE		Ultra 160 SCSI LVD/SE	
Interface configuration	68-pin High density connector			
Native capacity	0.28TB	0.4TB	0.8TB	1.6TB
Compressed capacity	0.73TB *2.6:1 compression	1.04TB *2.6:1 compression	2.08TB *2.6:1 compression	4.16TB *2.6:1 compression
Native sustained transfer rate	4MB/s	6MB/s	12MB/s	24MB/s
MSBF (Mean Swaps Between Failures)	1 million times or more			
Power requirements	AC100-240V ±10%, 50/60Hz			
Power consumption	40W		45W	
Dimensions (Excluding projection)	170(W) x 224(H) x 350(D)mm			
Weight	7kg (with 1 drive)			
Main features	<ul style="list-style-type: none"> -High density desktop solution -Easy operation (Cleaning, Disaster recovery) -Compact and space-saving -Dust-proof filter 			
Indicators	<ul style="list-style-type: none"> -2 7-SEG LEDs, 2 LEDs(Error/Warning, Cleaning) -2-button keypad -Display status of library and drive -Display error code of library and drive -Display warning code of library 			

*2.6:1 data compressed with ALDC. The data compression rate varies according to the type of data and the rate is generally lower if the data has already been compressed.

*1kByte=1000Byte, 1MByte=1000kByte, 1GByte=1000MByte, 1TByte=1000GByte basis